

1.25Gbps/155Mbps SFP 광모듈

Small Form-Factor Pluggable Transceivers



SFP-LX



SFP-LXWA20



SFP-SX



SFP-1000T



SFP+10G-LR



SFP+10G-LR-WA



SFP+10G-SR



SFP+10G-LR-WB

주문정보

※ 장거리 별도문의

	모델명	전송속도	파장	온도	광케이블	전송거리
Giga	SFP-LX	1.25 Gbps	1310nm	0~70℃	Single Mode	20km
	SFP-LXH	1.25 Gbps	1310nm	-40~80℃	Industrial Single Mode	10km
	SFP-SX	1.25 Gbps	850nm	0~70℃	Multi Mode	220m/550m
	SFP-SXH	1.25 Gbps	850nm	-40~80℃	Industrial Single Mode	220m/550m
	SFP-SX2	1.25 Gbps	1310nm	0~70℃	Multi Mode	2km
	SFP-LXWA20	1.25 Gbps	1550nm/1310nm	0~70℃	Single Mode	20km
	SFP-LXWB20	1.25 Gbps	1310nm/1550nm	0~70℃	Single Mode	20km
	SFP-1000T	1000Base-T	-	0~70℃	-	100m
100Mbps	SFP-SM	155 Mbps	1310nm	0~70℃	Single Mode	20km
	SFP-MM	155 Mbps	1310nm	0~70℃	Multi Mode	2km
	SFP-SMWA20	155 Mbps	1550nm/1310nm	0~70℃	Single Mode	20km
	SFP-SMWB20	155 Mbps	1310nm/1550nm	0~70℃	Single Mode	20km

40G/10G SFP 광모듈

Small Form-Factor Pluggable Transceivers



40G QSFP+SR4

- QSFP+ MSA
- IEEE 802.3ba 40Gbase-SR4
- OM3 멀티케이블로 300m까지 전송
- 4 x 10Gbps Optical 850nm VCSEL
- 4 x 10Gbps Electrical I/O (XLPP)
- 전력 < 1.5W
- MPO(MTP) 커넥터 사용 (2코어)
- 디지털 진단 기능 지원



40G QSFP+LR4

- 전송거리 < 10km
- QSFP+ MSA
- IEEE 802.3ba 40Gbase-LR4
- 1271, 1291, 1311, 1331nm 파장의 4 x 10Gbps CWDM 채널
- 4 x 10Gbps Electrical I/O (XLPP)
- 전력 < 3.5W
- Duplex LC 커넥터 사용 (2코어)
- 디지털 진단 기능 지원

주문정보

	모델명	전송속도	파장	온도	광케이블	전송거리
40 Giga	QSFP+SR4	40 Gbps	850nm	0~70℃	Multi Mode	300m
	QSFP+LR4	40 Gbps	1270nm / 1290nm 1310nm / 1330nm	0~70℃	Single Mode	10km
10 Giga	SFP+10G-SR	10.31 Gbps	850nm	0~70℃	Multi Mode	300m
	SFP+10G-LR	10.31 Gbps	1310nm	0~70℃	Single Mode	10km
	SFP+10G-ER	10.31 Gbps	1550nm	0~70℃	Single Mode	40km
	SFP+10G-ZR	10.31 Gbps	1550nm	0~70℃	Single Mode	80km
	SFP+10G-LR-WA	10.31 Gbps	1550nm/1310nm	0~70℃	Single Mode	10km
	SFP+10G-LR-WB	10.31 Gbps	1310nm/1550nm	0~70℃	Single Mode	10km